

---Specifications Sheet---

Model Name	Mid HC-B
Recommended Situations	
Recommended room coverage	No Limit
Conference size	No Limit
Network	Analog PSTN
Microphone	
Sound pick up range	4m
Microphone response frequency	200-4000Hz
Buit-in Mic	1
Expandable Mic	N/A
Speaker	
Max output(dB)	No Limit
Speaker response frequency	200-4000Hz
Audio	
Full Duplex	√
Dynamic Noise Reduction (DNR)	√
Automatic Gain Control (AGC)	√
Call functions	LCD display,Caller ID,Ringtones, VIP ringtone,FLASH
Connectivity	
USB	USB 2.0
Bluetooth connectivity	BT Version:3.0 BT profile:HSP / HFP / A2DP Wiress output:Class 2 Max.communication distance:10m(32.8ft)
3.5mm audio	√
Package	
Dimensions	40x33x8cm
Weight	2.15kg
Accessories	Handset,AC adaptor, Power cord,Telephone cord, USB cable,3.5MM Audio cable,RCA cable (1pair),RCA Jack switch, English User's Manual
Environments	
Power Input	220V 50Hz AC
Operating temperature	5 - 40° c
Storage temperature	-20 - 55°c
Compliance	FCC / CE / RoHS / BQB