

---Specifications Sheet---

| Model Name | Mid 2-B |
|-------------------------------|---|
| Recommended Situations | |
| Recommended room coverage | 40m ² |
| Conference size | 15-18 persons |
| Network | |
| | Analog PSTN |
| Microphone | |
| Sound pick up range | 4m |
| Microphone response frequency | 200-4000Hz |
| Buit-in Mic | 3 |
| Expandable Mic | N/A |
| Speaker | |
| Max output(dB) | 89dB (0.5m(1.6ft)) |
| Speaker response frequency | 200-4000Hz |
| Audio | |
| Full Duplex | √ |
| Dynamic Noise Reduction (DNR) | √ |
| Automatic Gain Control (AGC) | √ |
| Call functions | |
| | LCD display,Caller ID,Ringtones, VIP ringtone,FLASH |
| Connectivity | |
| USB | USB 2.0 |
| Bluetooth connectivity | BT Version:3.0 BT profile:HSP / HFP / A2DP Wiress output:Class 2 Max.communication distance:10m(32.8ft) |
| 3.5mm audio | √ |
| Package | |
| Dimensions | 40x33x14cm |
| Weight | 2.15kg |
| Accessories | Handset,AC adaptor, Power cord,Telephone cord, USB cable,3.5MM Audio cable,English User's Manual Expandable Mic(2pcs) |
| Environments | |
| Power Input | 220V 50Hz AC |
| Operating temperature | 5 - 40° c |
| Storage temperature | -20 - 55°c |
| Compliance | |
| | FCC / CE / RoHS / BQB |