



MVOICE 1000 Series USB/Bluetooth Conference Speakerphone

For personal and small group conferencing

MVOICE 1000 series conference speakerphones are specially designed for small business conference room, home based worker etc. who need professional audio endpoint for web-conferencing and video conferencing, to replace the PCs and mobile phone's speaker and microphone with outstanding audio quality.

Easy Set Up

Easy connect to your PC or laptop via USB, works great with PC based communication softphone i.e Skype,Zoom etc.

- Wireless conference with Bluetooth

Support connection to mobile phone via Bluetooth, turn your mobile phone as a conference gateway anytime anywhere. (MVOICE 1000-B only)

10' Microphone Pick Up

Each one speakerphone can pick up the sound with a 10' x 10' range with crystal clear audio.

Clean and Crisp Audio Quality

Let the far end hear clearly with our advanced audio algorithm, intelligent noise cancellation and powerful audio output.

Wide Software Compatibility

Works with virtually every online video conferencing software with no need for additional drivers or proprietary connections.

Battery Built-in

The built -in Li-ion battery supports over 4 hours continuous talk time



SPECIFICATIONS	MVOICE 1000	MVOICE 1000-B
РНОТО		
Recommended Situations		
Recommended room coverage	10-15 m²	10-15m²
Conference size	3-5 persons	3-5 persons
Microphone		·
Sound pick up range	10ft (3m)	10ft (3m)
Microphone response frequency	30Hz-16KHz	30Hz-16KHz
Built-in Mic	3	3
Speaker		
Max output(dB)	83dB	83dB
Speaker response frequency	30Hz-16KHz	30Hz-16KHz
Audio		
Full Duplex	√	√
Dynamic Noise Reduction (DNR)	√	√
Automatic Gain Control (AGC)	√	√
Connectivity		
USB cable	√	\checkmark
Bluetooth connectivity	N/A	BT Version:3.0 BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:30meters
Package		
Unit Dimensions	Ф140 x 32mm	Ф140 x 32mm
Package Dimensions	245x170x50mm	245x170x50mm
Package Weight	0.5kg	0.5kg
Accessories	Protective Travel Case USB cable,English User's Manual	Protective Travel Case USB cable, English User's Manual
Environments		
OS requirements	Windows XP/ Vista/ 7/8/10 , Mac OS, Android	Windows XP/ Vista/ 7/8/10 , Mac OS, Android
Power Input	USB:5 V DC @ 300 mA Maximum	USB:5 V DC @ 300 mA Maximum
Operating temperature	5°C—40°C	5°C—40°C
Storage temperature	-30°C—55°C	-30°C—55°C
Rechargeable battery	N/A	Over 4-hours talk time
Compliance	FCC / CE / RoHS	FCC / CE / RoHS/BQB