



MVOICE 3000-W

2.4 GHz Wireless Conference Speakerphone

MVOICE 3000-W provides high quality audio conferencing without cumbersome wires draping over your conference room. Designed to work with web conferencing software (e.g. Skype, Webex, Zoom, Jabber, etc...), simply connect the receiver antenna to a USB port and you are ready to go with full duplex audio for all of your conferencing needs, whether Win 7, 8, or 10 ,Mac OS and Android. Ideal for 1-10 person table huddle room.

Benefits:

Wireless USB Connection

Completely wireless USB 2.0 connection with a >20m range over 2.4 GHz (Up to 10 times more bandwidth than Bluetooth!)

Easy Set Up

With MVOICE 3000-W you are getting the easiest solution possible. Simply plug the USB dangle into your computers USB port and start your conference.

Two Working Modes:

You can connect MVOICE 3000-W to your PC or conference system either by wired USB or wireless USB.

12' Microphone Pick Up

Pick up your entire table with a 12' x 12' pick up range with crystal clear audio.

Robust Audio Output

Hear the far end clearly with our advanced audio algorithm, intelligent noise cancellation and powerful audio output.

Wide Software Compatibility

Works with virtually every online video conferencing software with no need for additional drivers or proprietary connections.

Quick Charge Battery Built-in

The built -in battery supports over 8 hours continuous talk

SPECIFICATIONS	MVOICE 3000-W
PHOTO	
USB Wireless Dongle	
Wireless frequency	2.400~2.4835 GHz
Transmitted power	Up to 14dBm
Receiving Sensitivity	-87dBm
RF impedance	50Ω
Microphone & Loudspeaker	
Sound pick up range	4 meters diameter distance
Microphone response frequency	30Hz-16KHz
Built-in Mic	3
Loudspeaker	1 x 5W
Speaker response frequency	30Hz-16KHz
Audio	
Full Duplex	√
Dynamic Noise Reduction (DNR)	√
Automatic Gain Control (AGC)	√
Connectivity	
USB Wireless dongle	√
USB cable	√
Package	
Unit Dimensions	Φ140 x 32mm
Package Dimensions	245x170x50mm
Weight	0.5kg
Accessories	USB dongle, USB cable, Protective Travel Case, User Guide
Environments	
Compatibility OS	windows XP/ Vista /7/8/10, Mac OS, Andriod
Power Input	USB:5 V DC @ 300 mA Maximum
Operating temperature	5°C—40°C
Storage temperature	-30°C—55°C
Rechargeable battery	Over 8 hours
Compliance	FCC / CE / RoHS